

ELECTRICAL:

Input Voltage: 24VDC.
 Input Current: 1 Amp
 Connector: 5 pin Reverse Key Euro/Micro

ILLUMINATION:

Light Source: LED – 6 Colors & White
 LED Life: up to 100,000 hours.

- Compact Size
- Quick Disconnect
- 24VDC
- High Output LED's
- DIN Rail Mount Driver
- Highly Efficient optics provide tight collimated light

Color	$\lambda_{\text{Dominant}}$	$\lambda_{\text{Dominant}}$	Spectral Half- width $\Delta\lambda_{1/2}$	λ_{Peak}	Units
	Typ.	Range		Typ.	
Red	625/ 627	620.0-645.5	20	638	nm
Red- Orange	617	613.0-631.5	20	627	nm
Amber	590	584.0-597.5	14	592	nm
Green	530	519.5-560.5	35	522	nm
Cyan	505	489.5-520.5	30	503	nm
Blue	470	459.5-490.5	25	464	nm



PART NUMBER DESIGNATION: RL3.5 - XXX

XXX = SPECTRUM CODE – 470, 505, 530, 590
 617, 630 and WHI

3.5" Light Emitting Window

EXAMPLE: 3.5" Ring Light with RED 630nm LED's
 Part# RL3.5-630




Light includes LDM DIN rail mount constant current driver and 4 meter cable

Monster Lights have changeable lenses for matching the area of illumination with the working distance



- Monster Lenses Available
- 12 Degree Narrow (Standard)
 - 50 Degree Medium Angle
 - "F" Wide Angle (~70 Degree)



Contact us for product dimensions, LED color or LED life information