



SP 5.5" Series SPOT LIGHT

ELECTRICAL:

Input Voltage: 24VDC.
 Input Current: 1.5 Amps
 Connector: 5 pin Reverse Key Euro/Micro

- Compact Size
- Quick Disconnect
- 24VDC
- High Output LED's
- DIN Rail Mount Driver
- Highly Efficient optics provide tight collimated light

ILLUMINATION:

Light Source: LED – 6 Colors & White
 LED Life: up to 100,000 hours.

Color	$\lambda_{\text{Dominant}}$ Typ.	$\lambda_{\text{Dominant}}$ Range	Spectral Half- width $\Delta\lambda_{1/2}$	λ_{Peak} Typ.	Units
Red	625/ 627	620.0-645.5	20	638	nm
Red- Orange	617	613.0-631.5	20	627	nm
Amber	590	584.0-597.5	14	592	nm
Green	530	519.5-560.5	35	522	nm
Cyan	505	489.5-520.5	30	503	nm
Blue	470	459.5-490.5	25	464	nm



PART NUMBER DESIGNATION: **SP5.5- XXX**

XXX = SPECTRUM CODE – 470, 505, 530, 590
 617, 630 and WHI

5.5" Light Emitting Window

EXAMPLE: 5.5" Spot Light with RED 630nm LED's
 Part # SP5.5-630



Light includes LDM55 DIN rail mount
 constant current driver and 12 foot cable

Contact us for product dimensions, LED color or LED life information

Spectrum Illumination
1387 Spencer Woods
Muskegon, MI 49445
Phone 231-744-7077 Fax 231-744-7787
www.spectrumillumination.com